



Board Type

FR MDF

Fire Retardant medium density fibreboard (MDF), for use in locations where improved performance in reaction to fire is required.

- Product available with design double sided.
- Real wood veneer (textured or smooth).
- Eco-friendly paint and varnish with UV curing. Low percentage of VOC's.
- Standard or high gloss varnish.
- Applications: Wall and ceiling panels, partitioning. Suitable to hotel and leisure sector, medical and services.

Technical Features

Dimensions	2420x1200. Others upon request.
Thickness	12, 16 and 19mm
Density	820 kg/m3 (\pm 30 kg/m3), according to EN 323.
Dimensional Tolerances (length/width)	\pm 2mm, according to EN 324-1 standard.
Formaldehyde Content	Low emission of formaldehyde, Class E1.
Reaction to fire	B-s2,d0 according to EN13501-1

United Kingdom

Vicaima Ltd
Marlowe Avenue – Greenbridge Ind. Est.
Swindon. Wiltshire SN3 3JF
Tel: +44 01793 532333 | E-mail: info@vicaima.com



Other Countries

Vicaima Indústria de Madeiras e Derivados, S.A.
Apartado 9, 3730-953
Vale de Cambra, Portugal
Tel: +351 256 426 300 | E-mail: vicaima@vicaima.com

