



Board Type

PLYWOOD

Panel composed with several layers glued perpendicularly. Panel with high dimensional stability.

- Product available with design on one side.
- Real wood veneer (textured or smooth), foil or primed.
- Eco-friendly paint and varnish with UV curing. Low percentage of VOC's.
- Standard or high gloss varnish.
- Applications: Furniture, wall and ceiling panels, packaging, exhibitions and shop fitting.

Technical Features

Dimensions	2480x1200. Others upon request.
Thickness	12 and 15mm
Density	420 kg/m ³ , according to EN 323 standard.
Dimensional Tolerances (length/width)	According to EN 315 standard.
Formaldehyde Content	Low emission of formaldehyde, Class E1.

April 2017

Notes: Vicaima assumes, unless advised otherwise, that the customer is the holder of the copyright, patent design, design registration or any other industrial property right related to the images supplied to Vicaima.

www.vicaima.com

United Kingdom

Vicaima Ltd
Marlowe Avenue – Greenbridge Ind. Est.
Swindon. Wiltshire SN3 3JF
Tel: +44 01793 532333 | E-mail: info@vicaima.com



Other Countries

Vicaima Indústria de Madeiras e Derivados, S.A.
Apartado 9, 3730-953
Vale de Cambra, Portugal
Tel: +351 256 426 300 | E-mail: vicaima@vicaima.com

